

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 10-271449

(43)Date of publication of application : 09.10.1998

(51)Int.Cl.

H04N 5/93

G11B 20/10

H04N 5/92

(21)Application number : 09-085656

(71)Applicant : SONY CORP

(22)Date of filing : 20.03.1997

(72)Inventor : MIZUNO KIMIYOSHI
SHIMIZU YOSHINORI
HASEGAWA AKIRA
ISHIDA TAKAYUKI

(54) DATA REPRODUCING DEVICE AND DATA REPRODUCING METHOD

(57)Abstract:

PROBLEM TO BE SOLVED: To provide the data reproducing device and the data reproducing method where a normally reproduced image is obtained through a normal angle switching even when a plurality of multi-angle blocks are stored in a track buffer.

SOLUTION: On the occurrence of an angle switching event, when a non-seamless angle block is reproduced at a presentation side, a controller 11 executes non-seamless angle switching, when a nonseamless angle block is reproduced at the presentation side, a track buffer 4a terminates event processing of the angle switching. When a non-seamless angle block is not reproduced at the presentation side, the seamless angle switching is executed at the arrival of a border of an interleaved unit(ILVU) during reading of the seamless angle, and when the angle switching point is recognized at the presentation side, the event processing of an angle switching is controlled so as to terminate the angle switching event processing.

